

Walcom®

SLIM KOMBAT PRO

SLIM KOMBAT PRO

Kevlar® fiber & magnesium technology

The technical and construction features of the Slim Kombat, enriched by superior performance levels in terms of paint atomization and pattern size, and an even lower weight.

This is the new **SLIM KOMBAT PRO**, 280 grams of technology, performance and reliability.

- Body: die-casting magnesium and Kevlar fiber
- Trigger: Kevlar fiber
- Air cap: anodized aluminum
- Air cap ring: Kevlar fiber
- Nozzle: AISI 303 stainless steel
- Needle-spring: stainless steel
- Seal gaskets: self-lubricating PTFE (teflon)
- Weight: 280 g
- Operating air pressure:
HALO: range 0.5-2.5 bar (7.2-36 psi) / recommended at 2 bar (29 psi)
HVLP: range 0.5-2.5 bar (7.2-36 psi) / HVLP at 2 bar (29 psi)
- Air consumption:
HALO: 265 l/min at 2 bar / 9 cfm at 29 psi
HVLP: 315 l/min at 2 bar / 11 cfm at 29 psi
- Ø nozzle gravity feed:
1,0 - 1,1 - 1,2 - 1,3 - 1,4 - 1,5 - 1,7 - 1,8 - 1,9
- Air inlet pressure regulator with pressure gauge

HALO / HVLP available versions

ONLY 280 g

